



ZKL 3000 RC

- Protects a section of a track by simulating a train in section.
- Can be configured, controlled and monitored through the cloud platform MTinfo 3000 and MTinfo 3000 app.




IP	SIL	Communication	Operating temperature	Dimensions (mm) l x w x h	Weight
IP65	4	2G, 4G	-25 to +70 °C	1560 x 215 x 114	10.6kg

Back-up battery ZKL 3000 RC




IP	Battery type	Voltage (V)	Capacity (Wh)	Dimensions (mm) l x w x h	Weight	Operating temperature (charging)	Operating temperature (discharging)
IP65	Lithium-ion	6.4	19.2	185 x 30 x 30	417g	0 to +45 °C	-20 to +60 °C

External battery ZKL 3000 RC




IP	Battery type	Voltage (V)	Capacity (Wh)	Dimensions (mm) l x w x h	Weight	Operating temperature (charging)	Operating temperature (discharging)
IP65	Lithium-ion	6.4	576	270 x 246 x 174	7700g	-20 to +45 °C	-20 to +60 °C

Charger back-up battery ZKL 3000 RC



IP	AC input (VAC)	DC output	Operating temperature	Storage temperature
IP20	AC100-240V	7.3V (2A)	-20 to +60 °C	-40 to +85 °C

Charger external battery ZKL 3000 RC



IP	AC input (VAC)	DC output	Operating temperature	Storage temperature
IP20	AC180-240V	7.5V (6A)	-20 to +50 °C	-40 to +70 °C